



Product Video

CIRCLE FLAMER X-F3600

- \ Original innovation introduced by SHOWVEN®
- \ Never seen flame effects up to 3 rotation cycles
- \ Full cycle and half cycle mode switchable
- \ Up to 182 preset firing sequences
- \ Nozzle front design, safer for operator
- \ Stainless steel nozzle, reliable and durable
- \ Safety lock with switchable test mode
- \ Double electromagnetic valves design for additional safety
- \ Double pump ensure stable pressure
- \ Fitted with igniter signal interface, compatible with fireworks firing system
- \ Neutrik®powerCON TRUE1 in/out, Neutrik®3-pin & 5-pin DMX in/out

SPECIFICATIONS

- \ MODEL: X-F3600
- \ ROTATION MODE: FULL CIRCLE MODE/HALF CIRCLE MODE
- \ DIMENSION: 640×360×370mm
- \ WEIGHT: 30kg
- \ VOLTAGE: 220V/110V, 50/60Hz
- \ POWER: 380W
- \ CONTROL: DMX, Pyro
- \ INTERFACE: Neutrik®powerCON TRUE1 IN/OUT
Neutrik® 3-pin & 5-pin XLR IN/OUT
9V-60V Fireworks igniter signal port
- \ FLAME HEIGHT: up to 8-10m (no wind)
- \ ROTATE ANGLES: 1080° (up to 3 cycles)
- \ FUEL: ISOPAR-G, H, L, M; ISOPROPANEL
- \ FUEL TANK CAPACITY: 10L
- \ FUEL CONSUMPTION RATE: 60ml/s
- \ EXT. BATTERY POWERED: YES

