



Product Video

## SPARKULAR® II

- \ Adjustable effect up to 6m
- \ Low noisy mode switchable
- \ Optimized feeding structure, powerful motor, minimize the stuck risks
- \ Motor status real time monitoring, safer to use and easier problem diagnosis
- \ New generation output tube, better effect
- \ EU and US patented technology
- \ Aluminum top plate module, sturdy and durable
- \ Rainproof structure, can be used in rain
- \ Flat structure, better for stage layout
- \ 3.2" LCD color screen, user friendly operation
- \ Both DMX and wireless remote control
- \ Individual safety DMX address

For safety use, please don't touch sparks with hands or other flammable objects

### SPECIFICATIONS

- \ MODEL: BT11/BT12
- \ DIMENSION: 286×280×258mm
- \ WEIGHT: 9kg
- \ VOLTAGE: 220V(BT11)/110V(BT12), 50/60Hz
- \ WORK POWER: 500W
- \ EFFECT HEIGHT: HC8200 LARGE: 3-6m/MEDIUM: 2-4.5m/SMALL: 1.5-3m
- \ HOPPER CAPACITY: Appr. 300g
- \ CONTROL: DMX, Wireless
- \ INTERFACE: Neutrik®powerCON TRUE1 IN/OUT 3 and 5 pin DMX IN/OUT
- \ DMX channels:2
- \ CASING MATERIAL: Anti-flaming ABS + PC, Aluminum

