

## SPARKULAR II SPECIFICATIONS



SPARKULAR® II is a brand new upgrade based on patented SPARKULAR® platform combined with valuable feedbacks from our customers, latest technologies and our years of experiences,. Comparing with the SPARKULAR®, SPARKULAR® II with effect up to 6m, much lower noisy, more powerful feeding structure and real time motor status monitoring ensure less stuck and safer firing. 3.2" LCD color screen, touch keypad, flat structure design etc modern features makes it more user friendly when operating the system. It is an ideal choice for circumstance where low noisy output and higher spark effects are preferred.

### Features

- Adjustable effect up to 6m
- Low noisy mode switchable
- Optimized feeding structure, powerful motor, minimize the stuck risks.
- Motor status real time monitoring, safer to use and easier problem diagnosis
- New generation output tube, better effect
- EU and US patented technology
- Aluminum top plate module, sturdy and durable
- Rainproof structure, can be used in rain
- Flat structure, better for stage layout
- 3.2" LCD color screen, user friendly operation
- Both DMX and wireless remote control
- Individual safety channel

*For safety use, please don't touch sparks with hands or other flammable objects*

## Specifications

### Dimension

286×280×258mm

### Weight

9 kg

### Voltage

AC200-240VAC / AC100-120VAC, 50/60 Hz

### Power

500W

### Fountain Height

HC8200 LARGE: 3-6m

HC8200 MEDIUM: 2-4.5m

HC8200 SMALL: 1.5-3m

### Hopper capacity

Appr. 300g

### Control

DMX, Wireless

### Interface

NEUTRIK POWERCON TRUE1 IN/OUT

3 and 5 pin DMX IN/OUT

### DMX channels

2

### Casing material

Anti-flaming ABS + PC, Aluminum