

TECHNICAL DATASHEET

UE WIND 350 DMX

Item Code: UEWIM350

The UE WIND 350 DMX is compact, economical and low noise. It is intended for small and medium-sized fixed or mobile installations. It can be used individually or in groups independently, disseminated within the lighting. The speed variation can be controlled electronically locally and by DMX.

NOMENCLATURE:

- 1 x PowerCon cable 5m



55 cm





25 cm

TECHNICAL SPECIFICATIONS:

Size: Lg 25 x lg 50 x Ht 55 cm

Weight: 14 Kg

Electric Characteristics:

230V - 50/60Hz - 355W - 1.55A - IP 44

Comply with norm CE ERP 2015

CHARACTERISTICS:

Noise 66 dB / 3m indoors (high speed version). 110° vertical adjustment.

Possibility of hanging under structure. Integrated electronic speed variation.

Incorporates electronic control with Timer and DMX.

HEADS USABLE :	Powerful %	Range mt	Wind speed mt/sec	Noise dB
	25%	3m	1m/s	30dB
		6m	0.4m/s	30dB
	50%	3m	3m/s	55dB
		6m	2m/s	50dB
	75%	3m	4m/s	57dB
		6m	2m/s	53dB
	100%	3m	4.5m/s	60dB
		6m	2m/s	55dB

Manufactured in ALUMINIUM and STAINLESS, UE ST- Base 350 DMX is done for last. Each element was chosen for his quality and efficiency.

Universal Effects, La qualité et l'innovation Fabriqué en France