

## **TECHNICAL DATASHEET**

### **UE WIND 450 DMX**

Item Code: UEWIM450

The UE WIND 450 DMX is compact, economical and low noise. It is intended for small and medium-sized fixed or mobile installations. It can be used individually or in groups independently, disseminated within the lighting. The speed variation can be controlled electronically locally and by DMX.

#### **NOMENCLATURE:**

- 1 x PowerCon cable 5m



# 75 cm





### **TECHNICAL SPECIFICATIONS:**

Size: Lg 25 x lg 70 x Ht 75 cm

Weight: 20 Kg

Electric Characteristics:

230V - 50/60Hz - 355W - 1.55A - IP 44

Comply with norm CE ERP 2015

### **CHARACTERISTICS:**

Noise 66 dB / 3m indoors (high speed version). 110° vertical adjustment.
Possibility of hanging under structure.
Integrated electronic speed variation. Incorporates electronic control with Timer and DMX.

HEADS USABLE :	Powerful %	Range mt	Wind speed mt/sec	Noise dB
	25%	3m	1.8m/s	42dB
		6m	1.3m/s	40dB
	50%	3m	5.2m/s	58dB
		6m	1.8m/s	52dB
	75%	3m	5m/s	64dB
		6m	1.8m/s	60dB
	100%	3m	5.5m/s	66dB
		6m	2.5m/s	60dB

Manufactured in ALUMINIUM and STAINLESS, UE ST- Base 350 DMX is done for last. Each element was chosen for his quality and efficiency.

### Universal Effects, La qualité et l'innovation Fabriqué en France